

Ordinance #68

Be it Ordained by the Council of the Town of Ashland City, Tennessee that sidewalks must be installed on the following streets in Ashland City, Tennessee: Main, Frey, Cumberland, Sycamore, and Elizabeth.


Whereas, the City of Ashland City shall be enforcing a sidewalk code for any new construction at the expense of the developer or land owner that will be occurring in Ashland City, Tennessee on Main Street, Frey Street, Cumberland Street, Sycamore Street, and Elizabeth Street.

If a person is found in violation of this Ordinance there will be a \$50.00 (fifty dollar) a day fine after occupancy until the violation is corrected.

Said Ordinance shall take effect twenty (20) days after its final passage the public welfare requiring it.

Passed 1st Reading August 8, 1989

Passed 2nd Reading Sept. 12, 1989

Mayor 

Attest 
City Recorder

SPECIFICATIONS FOR
SIDEWALKS FOR THE TOWN OF ASHLAND CITY

1. Adequate grade level for sidewalk base.
2. Sidewalks will be not less than 4' in width.
3. Sidewalks will be not less than 4" in depth.
4. Sidewalks will have wire mesh installed - size 6-6-10-10.
5. When pouring concrete wire mesh will be lifted by hook to be suspended in center of concrete slab.
6. Concrete will be at least 3000 psi, Class A.
7. Expansion joints will be every 50 feet.
8. Provide 1/8" per foot for sidewalk slope.
9. There will be no steps.
10. Ramps will be according to State codes - incline 2" per foot.